

इंटरनेट

मानक

Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan

“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”

IS 10236-13 (1986): Procedure for basic climatic and durability test for optical instruments, Part 13: Dust test
[PGD 22: Educational Instruments and Equipment]



“ज्ञान से एक नये भारत का निर्माण”

Satyanarayan Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartrhari—Nitiśatakam

“Knowledge is such a treasure which cannot be stolen”

BLANK PAGE



Indian Standard

PROCEDURE FOR
BASIC CLIMATIC AND DURABILITY
TESTS FOR OPTICAL INSTRUMENTS

PART 13 DUST TEST

(First Reprint AUGUST 1997)

UDC 601.7 : 620.193.13

© Copyright 1987

BUREAU OF INDIAN STANDARDS
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

Indian Standard

PROCEDURE FOR BASIC CLIMATIC AND DURABILITY TESTS FOR OPTICAL INSTRUMENTS

PART 13 DUST TEST

Optical and Mathematical Instruments Sectional Committee, EDC 36

Chairman

DR R. HRADAYNATH

Representing

Ministry of Defence (IRDE), Dehra Dun

*Members*DR O. P. NIJHAWAN (*Alternate to*
Dr R. Hradaynath)

LT-GEN K. L. KHOSLA

The Institution of Surveyors, New Delhi

COL (DR) M. G. ARUR

Survey of India, Dehra Dun

SHRI S. P. ROY (*Alternate*)

COL M. S. BOPARAI

Directorate General of Armed Forces Medical
Service, Ministry of Defence, New Delhi
National Instruments Ltd, Calcutta

SHRI J. CHOUDHURI

SHRI A. K. GHOSHAL (*Alternate*)

SHRI M. M. GUPTA

Ministry of Defence (DGOF)

BRIG H. LAL

Ministry of Defence

COL N. MOUDGAL (*Alternate*)

SHRI D. B. MALIK

Directorate General of Technical Development,
New DelhiSHRI MOHAN JEET SINGH (*Alternate*)

CDR G. D. BHATT

Chief Hydrographer to the Government of India,
Dehra Dun

DR E. K. MURTHY

Central Scientific Instruments Organization
(CSIR), ChandigarhDR A. K. AGARWAL (*Alternate*)

SHRI C. NARAYANA RAO

Bharat Electronics Ltd, Machilipatnam

SHRI A. M. JOSE (*Alternate*)

SHRI P. N. PUNTAMBEKAR

National Physical Laboratory (CSIR), New Delhi

SHRI RAM PRASAD (*Alternate*)

SHRI J. K. SONEJA

All India Instrument Manufacturers' and Dealers'
Association, BombaySHRI C. L. BATRA (*Alternate*)

LT-COL ARUN KUMAR

Ministry of Defence

MAJ J. L. YADAV (*Alternate*)(*Continued on page 2*)

© Copyright 1987

BUREAU OF INDIAN STANDARDS

This publication is protected under the *Indian Copyright Act* (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

(Continued from page 1)

Members

SHRI H. C. VERMA

SHRI K. G. PURANG (*Alternate*)

SHRI M. K. VERMA

SHRI K. S. LAMBA (*Alternate*)

SHRI S. CHANDRASEKHARAN,
Director (Mech Engg)

Representing

Associated Instrument Manufacturers' (India) Pvt
Ltd, New Delhi

Development Commissioner, Small Scale Industries,
New Delhi

Director General, BIS (*Ex-officio Member*)

Secretary

SHRI S. K. PURI

Deputy Director (Mech Engg), BIS

**Panel for Basic Climatic and Durability Tests for Optical Instruments
EDC 36 : P-1**

Convener

SHRI BHAGWAN SINGH

Ministry of Defence (IRDE), Dehra Dun

Members

SHRI S. P. ROY

Survey of India, Dehra Dun

SHRI O. S. NAGAR (*Alternate*)

LT-COL L. S. KULHARI

Ministry of Defence (DGI), Dehra Dun

SHRI H. D. GANGAR (*Alternate*)

SHRI G. K. SACHDEV

Ministry of Defence (DGOF), Dehra Dun

SHRI A. K. GHOSHAL

National Instruments Ltd, Calcutta

DR. E. K. MURTHY

Central Scientific Instruments Organization (CSIR)
Chandigarh

DR A. K. AGARWAL (*Alternate*)

Indian Standard

PROCEDURE FOR BASIC CLIMATIC AND DURABILITY TESTS FOR OPTICAL INSTRUMENTS

PART 13 DUST TEST

0. FOREWORD

0.1 This Indian Standard (Part 13) was adopted by the Indian Standards Institution on 21 July 1986, after the draft finalized by the Optical and Mathematical Instruments Sectional Committee had been approved by the Mechanical Engineering Division Council.

0.2 Fast development in the field of instruments had brought a significant change in their basic content and design. It has been felt over the years that IS : 2352-1963* does not cater for the present day needs of the instruments and is also not in line with the recent trends in climatic and environmental testing procedures to be adopted for improving their quality and reliability. It has, therefore, become necessary to have uniform and more rational testing procedures as far as possible. This series of standards on climatic and durability test (IS : 10236) has been prepared with this objective.

0.2.1 It is proposed to withdraw the existing Indian Standard (IS : 2352-1963*) as soon as the tests mentioned therein are covered in the new series of IS : 10236.

1. SCOPE

1.1 This standard (Part 13) covers the procedure for conducting dust test for optical instruments.

2. TERMINOLOGY

2.1 For the purpose of this standard, the definitions given in IS : 10236 (Part 1) † shall apply.

*Procedure for basic climatic and durability tests for optical instruments.

†Procedure for basic climatic and durability tests for optical instruments: Part I General. (*under preparation*).

3. OBJECT

3.1 The object of this test is to determine the suitability of optical instruments to withstand the abrasive action of dust and other conditions such as encountered in dusty atmosphere.

4. INITIAL MEASUREMENTS

4.1 The instrument shall be visually examined, and optically, electrically and mechanically checked as required by the relevant instrument specification.

5. TEST CHAMBER

5.1 The chamber used for this test shall have characteristics as specified in 5.1.1 to 5.1.7.

5.1.1 The chamber shall be capable of circulating dust in its working space as to produce a dust concentration specified under 5.1.5.

5.1.2 It shall also be capable of maintaining its working space at a temperature desired by the required severity with a tolerance of $\pm 3^{\circ}\text{C}$ and relative humidity not exceeding 50 percent even when there is no agitation of dust in the chamber.

5.1.3 The dust used for this test shall be dry. If slight moisture is anticipated the dust shall be heated outside to a temperature near to the specified severity before the commencement of the test. A sufficient quantity of dust shall also be made available in the chamber in order to obtain specified dust concentration throughout the test.

5.1.4 The dust used in the chamber shall have the physical characteristics and composition as given below.

5.1.4.1 Physical characteristics

- a) 100 percent dust shall pass through sieve having aperture size of $150\ \mu\text{m}$
- b) 98 ± 2 percent dust shall pass through sieve having aperture size of $110\ \mu\text{m}$
- c) 90 ± 2 percent dust shall pass through sieve having aperture size of $75\ \mu\text{m}$
- d) 75 ± 2 percent dust shall pass through sieve having aperture size of $46\ \mu\text{m}$

See IS : 460
(Part 1)-1985*

*Specification for wire cloth test sieves (third revision).

5.1.4.2 Composition

<i>Substance</i>	<i>Percent by Weight</i>
SiO ₂	97 to 99
Fe ₂ O ₃	0 to 2
Al ₂ O ₃	0 to 1
TiO ₂	0 to 2
MgO	0 to 1
Ignition losses	0 to 1

5.1.5 A simple dust concentration measuring device is shown in Fig. 1. Dust enters the box through the five circular holes and collects at the bottom of the detachable cover. For measuring dust concentration, the device shall be placed in any representative position (where the effect of dust on the specimen is maximum) within the dust chamber. The air shall be circulated for five minutes and the dust shall be allowed to enter and settle down at the bottom of the device. The amount of dust collected on the detachable cover inside the device shall be 25 ± 5 grams.

5.1.6 It shall have provision to supply electric power to the specimen under test from an external source.

5.1.7 To see functioning of the instrument, when required, the chamber shall have a provision of suitable viewing window.

6. TEST SEVERITIES

6.1 The severity indicated by temperature and duration shall be as specified in the relevant instrument specification. The value may be selected from those given below:

- | | | |
|--|---|---------------------------|
| a) 50°C \pm 3°C for 2 hours | } | R.H. less than 50 percent |
| b) 40°C \pm 3°C for 1 hour | | |
| c) 40°C \pm 3°C for $\frac{1}{2}$ hour | | |

7. TEST PROCEDURE

7.1 The instrument shall be subjected to this test in the unpacked and switched off condition.

7.2 While at the laboratory temperature the instrument shall be introduced into the chamber, the latter also being at the laboratory temperature.



:

7.3 The temperature of the chamber shall then be raised to the specified value given in 6.1 or any other value specified by the relevant instrument specification. The relative humidity shall be maintained at a value not exceeding 50 percent.

7.4 After the temperature equilibrium is reached the instrument shall be subjected to the stream of dust laden air for a period as given in 6.1 or any other period specified in the relevant instrument specification.

7.5 If required by the relevant instrument specification, the instrument shall be switched on and a performance check shall be carried out at any time during the period specified in 7.4.

7.6 The circulation of dust shall then be stopped and the temperature of the chamber shall be restored to the laboratory atmospheric conditions.

7.7 Recovery — The instrument shall then be removed from the chamber and kept under standard atmospheric conditions for recovery for not less than one hour nor more than two hours.

8. FINAL MEASUREMENTS

8.1 After recovery the accumulated dust shall be removed before the observations are made. The dust shall be removed by brushing, wiping or shaking. Under no circumstances shall the dust be removed by an air blast or by vacuum cleaning.

8.2 The instrument shall be visually examined for any deleterious effects on optical and other surfaces, finishes and markings and for ease of working of moving parts; its performance shall also be checked in accordance with the relevant instrument specification.

9. DETAILS TO BE GIVEN IN RELEVANT INSTRUMENT SPECIFICATION

9.1 The relevant instrument specification shall state the following for carrying out this test:

- a) Initial observations/measurements;
- b) Test severity;
- c) Test position for the instrument, if important;
- d) Performance check while under operation, if required;
- e) Final observations/measurements; and
- f) Any deviation from the normal procedure.

BUREAU OF INDIAN STANDARDS

Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002

Telephones: 323 0131, 323 3375, 323 9402

Fax: 91 11 3234062, 91 11 3239399, 91 11 3239382

Telegrams : Manaksanstha

(Common to all Offices)

Telephone

Central Laboratory:

Plot No. 20/9, Site IV, Sahibabad Industrial Area, Sahibabad 201010

8-77 00 32

Regional Offices:

Central : Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002 323 76 17

*Eastern : 1/14 CIT Scheme VII M, V.I.P. Road, Manikola, CALCUTTA 700054 337 86 62

Northern : SCO 335-336, Sector 34-A, CHANDIGARH 160022 60 38 43

Southern : C.I.T. Campus, IV Cross Road, CHENNAI 600113 235 23 15

†Western : Manakalaya, E9, Behind Marol Telephone Exchange, Andheri (East), MUMBAI 400093 832 92 95

Branch Offices:

'Pushpak', Nurmohamed Shaikh Marg, Khanpur, AHMEDABAD 380001 550 13 48

‡Peenya Industrial Area, 1st Stage, Bangalore-Tumkur Road, BANGALORE 560058 839 49 55

Gangotri Complex, 5th Floor, Bhadbhada Road, T.T. Nagar, BHOPAL 462003 55 40 21

Plot No. 62-63, Unit VI, Ganga Nagar, BHUBANESHWAR 751001 40 36 27

Kalaikathir Buildings, 670 Avinashi Road, COIMBATORE 641037 21 01 41

Plot No. 43, Sector 16 A, Mathura Road, FARIDABAD 121001 8-28 88 01

Savitri Complex, 116 G.T. Road, GHAZIABAD 201001 8-71 19 96

53/5 Ward No.29, R.G. Barua Road, 5th By-lane, GUWAHATI 781003 54 11 37

5-8-56C, L.N. Gupta Marg, Nampally Station Road, HYDERABAD 500001 20 10 83

E-52, Chitaranjan Marg, C-Scheme, JAIPUR 302001 37 29 25

117/418 B, Sarvodaya Nagar, KANPUR 208005 21 68 76

Seth Bhawan, 2nd Floor, Behind Leela Cinema, Naval Kishore Road, LUCKNOW 226001 23 89 23

NIT Building, Second Floor, Gokulpat Market, NAGPUR 440010 52 51 71

Patliputra Industrial Estate, PATNA 800013 26 23 05

Institution of Engineers (India) Building 1332 Shivaji Nagar, PUNE 411005 32 36 35

T.C. No. 14/1421, University P. O. Palayam, THIRUVANANTHAPURAM 695034 6 21 17

*Sales Office is at 5 Chowringhee Approach, P.O. Princep Street, CALCUTTA 700072 27 10 85

†Sales Office is at Novelty Chambers, Grant Road, MUMBAI 400007 309 65 28

‡Sales Office is at 'F' Block, Unity Building, Narashimaraja Square, BANGALORE 560002 222 39 71